



4,000-Lb. LITTELL
40-12 Auto Centering
Reel



6,000-Lb. LITTELL
Auto Centering Reel



VAMCO Quantron
6 Servo Feed



LITTELL Feed



400 Ton HPM 400II
Horizontal Die Casting
Press



SCHAEFER Electric
Reveberatory Furnace



LITTELL 2-17 Precision
Powered Straightener



1 Ton GAFFEY Jib
Crane with Jet Trolley



MATTISON 48" x 17" Reciprocating
Table Surface Grinder



MATTISON 72" x 24" Reciprocating
Table Surface Grinder



CINCINNATI 340-20 Twin Grip
Centerless Grinder

DIRECTIONS FROM TULSA INTERNATIONAL AIRPORT TO FRANKLIN ELECTRIC CO.

Take OK-11 east toward Tulsa/Joplin

Follow signs for I-244E/US-412/US-169/Joplin and merge onto I-244E/412E

Take 412E to S Carl Street turning right

Take 1st left onto W Quarter Road, plant will be on your left

650 Highway 412 West
Siloam Springs, AR 72761

FOR FURTHER INFORMATION:

To speak with a sales representative
about this sale, please contact:
John Bopp at +1 (708) 606-3240
john@perfectionindustrial.com



TERMS & CONDITIONS

A 16% Buyer's Premium will be charged.

ALL PAYMENTS MUST BE MADE BY WIRE TRANSFER,
CASHIER'S CHECK OR COMPANY CHECK SENT TO
PERFECTION INDUSTRIAL SALES HEAD OFFICE. ANY BUYERS
INTENDING TO SPEND OVER \$25,000.00 MUST SEND A
BANK LETTER GUARANTEEING PAYMENT TO PERFECTION
INDUSTRIAL SALES. THE BANK LETTER MUST BE RECEIVED
BY WEDNESDAY, JUNE 15th.

The following example can be used for reference: Mr. "Buyer
Name" is a customer of this bank. This bank will guarantee
unqualified payment to Perfection Industrial Sales up to the
amount of \$..... This letter is good and valid until
July 1st, 2011.

Although all information has been obtained from sources deemed
reliable, Perfection Industrial Sales and seller make no warranty
or guarantee, expressed or implied, as to the accuracy of the
information contained in this brochure. It is for this reason buyers
should inspect the equipment prior to purchase. Perfection
Industrial Sales reserves the right to withdraw items, alter the
order of sale and accept bids from the seller.

Please see www.perfectionindustrial.com for full terms and
conditions.

AXP/1050592

FOR FURTHER INFORMATION:
To speak with a sales representative
about this sale, please contact:
John Bopp at +1 (708) 606-3240
john@perfectionindustrial.com



Perfection Industrial Sales
2550 Arthur Ave.
Elk Grove Village, IL 60007
888.241.4577 (U.S. & Canada)
847.427.3333 (outside U.S. & Canada)
847.427.8884 (fax)
www.perfectionindustrial.com



Perfection Industrial Sales

ONLINE AUCTION SALE

Minster, Bliss & Oak
High Speed Presses, Lamination Equipment,
Die Casting, Grinding & Facilities Support

Assets for Sale Due to the Continuing Operations of
Franklin Electric Co., Inc.

Location:
650 Highway 412 West
Siloam Springs, AR 72761

Sale Date: June 16, 2011
Sale Closing: 2:00 PM Central



Perfection Industrial Sales
847-427-3333 Main office sales@perfectionindustrial.com
847-427-8884 Fax www.perfectionindustrial.com

IN ASSOCIATION
WITH:

Hilco Industrial, LLC
Auctioneers - Liquidators - Appraisers

Maynards
SINCE 1900

Presorted
First-Class Mail
U.S. Postage
PAID
Twin Cities, MN
Permit #93723



Perfection Industrial Sales
847-427-3333 Main office sales@perfectionindustrial.com
847-427-8884 Fax www.perfectionindustrial.com

IN ASSOCIATION
WITH:

Hilco Industrial, LLC
Auctioneers - Liquidators - Appraisers

Maynards
SINCE 1900

To Return Maximum Value For Your Assets – Insist on Perfection

Buy

Sell

Rent

Auction

Appraisals

Liquidations

Investment Recovery

Finance



20,000-Lb. COE 20048 Uncoiler with Coil Cart



MINSTER E2-300-84-44 Hevistamper Straight Side, High Speed Press



MINSTER PM3-300-70 Straight Side, High Speed Press



MINSTER P2-200-48 Piecemaker Straight Side, High Speed Press



MINSTER P2-200-48 Piecemaker Straight Side, High Speed Press



OAK 48-LP-200-449 Straight Side, High Speed Press



MINSTER P2-150-60 Piecemaker Straight Side, High Speed Press



MINSTER P2-150-60 Piecemaker Straight Side, High Speed Press



BLISS HP2-150-60 Straight Side, High Speed Press



WELLMAN Roller Hearth Furnace



2,500-Lb. LITTELL 25-12 Auto Centering Reel



4,000-Lb. MAX LIFT Coil Upender



MINSTER MMHS 10-14-40 Stock Straightener



PERFECTO 500-48 CGCF Feed



5 Ton OMI Bridge Crane with Electric Hoist



½ Ton GORBEL Jib Crane with Yale ½ Ton Hoist



WELLMAN Roller Hearth Furnace

(8) HIGH SPEED MECHANICAL PRESSES

MINSTER E2-300-84-44 Hevistamper Straight Side, High Speed Press; S/N. 19590; (1972); 300 Ton Capacity; 1.5" Stroke; 23" Shut Height; 5" Adjustment; 91" x 44" Bed Area; 0 – 225 VSPM; Orchid Quick Lifts Die System

MINSTER PM3-300-70 Straight Side, High Speed Press; S/N. 27289; (1988); 300 Ton Capacity; 1.25" Stroke; 3" Adjustment; 25.75" Shut Height; 72" x 32" Bed Area; 0 – 500 VSPM

MINSTER P2-200-48 Piecemaker Straight Side, High Speed Press; S/N. 22544; (1975); 200 Ton Capacity; 1" Stroke, 20" Shut Height; 3" Adjustment; 48" x 44" Bed Area; 0 – 350 VSPM

MINSTER P2-200-48 Piecemaker Straight Side, High Speed Press; S/N. 19440; (1970); 200 Ton Capacity; 1" Stroke, 20" Shut Height; 3" Adjustment; 48" x 42" Bed Area; 175 – 350 VSPM

MINSTER P2-150-60 Piecemaker Straight Side, High Speed Press; S/N. 19828; (1971); 150 Ton Capacity; 1.5" Stroke; 22.5" Shut Height; 4" Adjustment; 60" x 44" Bed Area; 0 – 330 VSPM

MINSTER P2-150-60 Piecemaker Straight Side, High Speed Press; S/N. 19047; (1970); 150 Ton Capacity; 1.5" Stroke; 22.5" Shut Height; 4" Adjustment; 60" x 40" Bed Area; 0 – 330 VSPM

BLISS HP2-150-60 Straight Side, High Speed Press; S/N. H-55308; 150 Ton Capacity; 1.5" Stroke; 22" Shut Height; 4" Adjustment; 60" x 36" Bed Area; 0 – 250 VSMP; Quick Die Change Hydraulic Lifts System

OAK 48-LP-200-449 Straight Side, High Speed Press; S/N. 48-LP-200-449; 200 Ton Capacity; 1" Stroke; 20.5" Shut Height; 4" Adjustment; 48" x 30" Bed Area; 150 – 400 VSPM

COIL HANDLING EQUIPMENT: (8) UNCOILERS & UPENDER

20,000-Lb. COE 20048 Uncoiler with Coil Cart; S/N. 4201-1; 20,000 Lb. Max Material Weight; 16" ID; 54" Max OD

6,000-Lb. LITTELL Auto Centering Reel; S/N. 94769-01; 6,000 Lb. Max Coil Weight; 19"-24" ID Range; 60" Max OD; 12" Max Material Width

4,000-Lb. MINSTER 4-14D Auto Centering Reel; S/N. 1370065; 4,000 Lb. Max Coil Weight; 16"-20" ID Range; 60" OD

4,000-Lb. LITTELL 40-12 Auto Centering Reel; 4,000 Lb. Max Coil Weight; 15"-20" ID Range; 60" OD; 12" Max Coil Width

2,500-Lb. LITTELL 25-12 Auto Centering Reel; S/N. S-3966-75-2; 2,500 Lb. Max Coil Weight; 15"-20" ID Range; 48" Max OD; 12" Max Material Width

2,500-Lb. LITTELL Auto Centering Reel; S/N. S-7544-76; 2,500 Lb. Max Coil Weight; 15"-20" ID Range; 60" OD

2,500-Lb. LITTELL 25-12 Auto Centering Reel; S/N. S-7564-75; 2,500 Lb. Max Coil Weight; 15"-20" ID; 60" OD; 12" Max Material Width (2 Available)

4,000-Lb. MAX LIFT Coil Upender

(6) POWERED STRAIGHTENERS

LITTELL 212-17 Precision Powered Straightener; S/N. 90929-93; .090" Max Material Thickness x 12" Wide; 200' Per Minute (4 Available)

LITTELL 2-17 Precision Powered Straightener; S/N. 94768.01; .090" Max Material Thickness; 12" Max Material Width; 250' Per Minute Max Speed

LITTELL Precision Powered Straightener; .090" Max Material Thickness; 6" Max Material Width

LITTELL Precision Powered Straightener; S/N. 8192075; .090" Max Material Thickness, 12" Max Material Width

LITTELL Quantum 250 Precision Powered Straightener; 8" W x .090" Approx. Thickness

MINSTER MMHS 10-14-40 Stock Straightener; S/N. 12-11151; .060" Max Material Thickness; 13.5" Max Material Width; 2400 IPM

(8) MATERIAL FEEDS

VAMCO Quantron 6 Servo Feed; S/N. 662.52C728; (2006); .125" Max Material Thickness; 6" Max Material Width

VAMCO Quantron 6 Servo Feed; S/N. 662.52C728; (2006); .125" Max Material Thickness; 6" Max Material Width

VAMCO Van Mark 8 Feed; S/N. VS88238606R; Approx .090" Max Material Thickness; 6" Max Material Width

SANKYO V230 Variax Adjustable Cam Feed; S/N. V41545; 12" Max Material Width; L-R Feed Direction

LITTELL Feed; S/N. 78446-71; .090" Max Material Thickness x 12" Wide; 200' Per Minute

LITTELL Feed; Approx. .090" Max Material Thickness, 12" Max Material Width (2 Available)

LITTELL Feed; S/N. 78585-71; .090" Max Material Thickness; 6" Max Material Width

PERFECTO 500-48 CGCF Feed; S/N. CG-87145; 48" Max. Material Width

(3) GRINDING MACHINES

MATTISON 72" x 24" Reciprocating Table Surface Grinder; Travatrol 6RC17A Magnetic Chuck Control, Dual 24" x 36" Magnetic Chucks; 59 HP

MATTISON 48" x 17" Reciprocating Table Surface Grinder; Travatrol TRS4B-1 Magnetic Chuck Control; 24.5 HP

CINCINNATI 340-20 Twin Grip Centerless Grinder; 18" Dia Grinding Wheel; 13" Dia Regulating Wheel for 7 Degree Swivel; 14" Dia Regulating Wheel for 6 Degree Swivel; with Entrance and Exit Conveyor

DIE CAST MACHINERY

400 Ton HPM 400II Horizontal Die Casting Press; Used to Diecast cores 2.88-6.75" in length; 4 Parts per cycle

SNAIR Y Auto Aluminum Ladle; Transfers Molten Aluminum for Furnace to Diecast Machine

WELLMAN Roller Hearth Furnace; S/N. 7541; Natural Gas; 3,230,300 BTU/Hour; .65 SG; 6 Zone Oven; Zone 1-1,000F; Zone 2-1,000F; Zone 3-1,600F; Zone 4-1,600F; Zone 5-1,200F; Zone 6-900F; 1' x 4' Opening

WELLMAN Roller Hearth Furnace; S/N. 01-106-RH-01; Natural Gas; 3,230,300 BTU/Hour; .6 SG; 5 Zone Oven; Zone 1-1,200F; Zone 2-1,600F; Zone 3-1,600F; Zone 4-1,400F; Zone 5-1,200F; 1' x 4' Opening

SCHAEFER Electric Reveberatory Furnace; Aluminum Melt Furnace which uses ceramic heating elements; 400 Lbs. per hour

LECTODRYER LLT-50 Exalene Gas Chiller; S/N. 97159128; 1 PSIG; R-22 Refrigerant; 53 PSIG Suction (2 Available)

OVERHEAD & JIB CRANES

5 Ton OMI Bridge Crane with Electric Hoist; 28' x 40' Span; Spacemaster SX Trolley with R&M 5 Ton Hoist

1 Ton GAFFEY Jib Crane with Jet Trolley (No Hoist)

½ Ton GORBEL Jib Crane with Yale ½ Ton Hoist; Mounted to Girder

ALSO AVAILABLE:

Huge quantities of heavy duty roller conveyors, various sizes.

