

Online Auction Sale

By Order of A Plus Machinery & Rigging Due to Relocation

105,000 Sq Ft Building on 3.9 Acres, Mobile Plant Equipment, Rigging Equipment, Power Tools,

Machine Tools & Tooling

Property

105,000 Square Foot Building Sitting on 3.995 acres. Main Building consists of 73,000 square foot masonry structure with 18' ceilings and a 32,000 square foot metal building with 24' ceiling in the rear. There is about 8,000 square feet of office space divided between two floors. The entire facility has 12" reinforced concrete floors with (4) loading docks.

Mobile Plant Equipment

Drott 25 Ton Crane System, 2 Hoists. Turning Radius - 18', Lowest Travel Height - 9'6", Drive-Steer Axle Combinations - 2 Stage Hydraulic Chain Drive, Full Cab Enclosure, Cab Heat and Fans, Equipped with Industrial Crane Unit, Diesel Power, Auto Trans.

Broderson 8 1/2 Ton Crane, Capacity @ 6'7" Reach - 20000 LBS, Capacity @ 28'2" Reach - 8500.00, Turning Radius - 18', Lowest Travel Height - 9', Drive-Steer Axle Combinations - 2 Stage Hydraulic, Full Cab Enclosure, Cab Heat and Fans, Outriggers – Front Hyd Outriggers, Tires - Dual In Front Single Steer, Rear Outriggers, Hydraulic, Boom Options - 45 Deg Left and Right, Motor - 492 John Deere Diesel, Transmission - C7 Ford Automatic, Equipped with: Industrial Crane Unit, John Deere Diesel 492, Auto Trans, Front Out Riggers, Rear Out Riggers

Grove 68IND Hydraulic Crane, SN. 22297, 10 Ton Capacity, Hydraulic Out, Riggers Lift and Walk, Dome Lights, Air Breaks, Heater, Air Tires

Rigging Equipment

Hyster 15,000 Lb Cap. Fork, Short Mast, Width - 96", Length - 148.8", Total Height - 96", Fork Height - 118", Fork Length - 14", Engine - 6 CYL Gasoline, Mast - 2 Stage, Air Tires

Caterpillar 12,000 LB Forklift, 53.9" Wide 148.8" Long, 82.5" Total Height, 118" Fork Height, 72", LP, Double Mast, Hard Tires

Hobbs ACC100RC LPS Forklift, 10,000 Lb Capacity, 42" Forks, 105" Lift Height, Dual Mast, Solid Tire, Overhead Protection

Komatsu FG45S-6 9,900 LB Capacity Forklift, 53.9" Wide, 148.8" Long, 82.5" Total Height, 118" Fork Height, LP, Double Mast, Hard Tires

Hyster 4,750 Lb Cap LP Forklift, SN. C187V118505, Triple Mast, 42" Forklifts, Side Shift, Solid Tire, Overhead Protection

Industrial Air Caster 80K Lb Cap, 9' Turning Radius, 6" Lowest Travel Height, Drive-Steer Axle Combinations - Air Drive Handler, Drive Hook Ups, Interchangeable Air Bags, Machine floats on 1/4 inch of air pressure across the floor.

Crown Sideshifter Forklift, SN. 1A128785, 3,700 Lb Lift Capacity, 190" Lift Height

Hydraulic 10,000 LB Boom

Large Quantity of Rigging Accessories Including Rigging Chains of assorted thicknesses, Rigging Cables, U Bolts, Tie Downs, Rigging Skates and Porto-Powers.

Machinery

Mazak Powercenter V-15N, NC/CNC 3 axis with 55" x 30" table, 5,000 lbs max table load

Cincinnati Millacron 550-20 Plain Vercipower, 18" x 118" Table, 80" X Travel, 30" Y Travel, 18" Z, 25-1500 Spindle RPM, 50 Taper, 20HP, 18,000 Lbs.

Niigata NE250U Ton Injection Molder, (1993) 14 oz Shot, horizontal/vertical with core pull, Voltage 460/3/60

Toshiba ISF 120SII-5A 120 Ton Injection Molder, (1993) 5 oz Shot Size Hydraulic, Platen Size - 24.80" x 22.80", Daylight/Maximum - 27.60", Minimum Mold Height - 5.90", Maximum Mold Height - 15.70", Distance between tie bars - 16.10" x 14.20", Tie Rod Diameter - 2.80", Maximum Ejector Stroke - 2.80", Dimensions - 226.3' x 47.3' x 81", Weight - 13,050 LBS.

(4) 3.93 Ton Margnum HBM-4B C-Frame Press, 10" Stroke, 2" Ram Bore, 2,500 PSI, with Micro Panel D830 DRO, SN. 99160, PLC PLC Controls, Stand, Dual Palm Buttons.

Bridgeport Series I MDI Milling Machine, Machine Center Vert NC/CNC 3 Axis. Table Size - 16 x 35", X-Axis (Cross/Long)- 30", Y-Axis (Saddle)- 16", Z-Axis (Spindle/Vertical) - 20", Spindle Speed - 3,500 RPM, 2 HP Motor, Taper - 30 Tool Changer Positions - 0, Heidenhain TC 311 Controls.

Manex Mill #2, Manex Verical Jig Bore. 12.5" x 51" Table Size, 33.5" Longitudinal Table Travel, 10" Table Cross Travel, 3" Knee Vertical Quill Travel, Table Size - 14 x 35", Travels/Longitudinal - 30", Cross - 12", Quill - 9", Max Vert. Dist. Spindle to Table - 24", Throat Depth - 12", Speeds - 37 - 1800 RPM, Longitudinal Table Travel - 30" Cross Table Travel - 9", Vertical Knee Travel - 18", Vertical Head Travel - 16", Longitudinal & Cross Feeds 3/8"-90"/MIN, Vertical Feeds - 3/16"-45"/MIN, Longitudinal & Cross Traverse - 150"/MIN, Vertical Feeds - 75"/MIN, Spindle Taper - Moore Threaded Taper, Spindle Speeds - 15-1500 RPM, Motor - 5 HP, Electrics - 230/460/3PH, Dimensions - 114 x106 x116, Verical Spindle Motor - 7.5 HP, (16) Horizontal Spindle Speeds - 56 to 1800 RPM, Horizontal Spindle Motor - 7.5 HP, Horizontal Spindle Taper - ISO 50, Longitudinal Feed Range - 1/2 to 55 IPM, Cross Feed Range - 3/8 to 35 IPM, Vertical Feed Range - 3/16 - 18 IPM, Dimensions - 70"L-RX77"BX83"H, Weight - 6500 LBS. Equipped with: Power Feed to Table and Cross Feed, Power Feed to Head.

Supermax Mill, Model YC-1 1/2 V, 80-2720 SPM, 9" 42" Table

Adrain Mill, Model HD ACE, COLLET 5 C, Wheel Size - Up to 6", Wheel RPM - 3450 RPM, Width of Wheel - Up to 3", Max. Large Diameter - 15", Vertical Travel - 10", Cross Travel Head - 14", In & Out Travel - 8",

Clausing 4 Head Drill Press, 150-2000 SPM, 2' x 80" Table

Large Quantity of Tooling Including Multiple Spindle Drill, Tape and Mill units, Wisconsin Drill and Tap Heads, Boring Bars, Boring Sleeves, Drill Holders, Carbide Inserts, Form, Face & Drill Shank, 50 Taper Collet Chucks, Tapping Chucks, 50 Taper Rigibore Tooling, 40 Taper Tool Holders, Boring Heads and Tap Drivers, Hard and Soft Jaw Chucks, Carbide Insert Face Mills, large assortment of Hydraulic Cylinders and Air Cylinders, Rotary Indexers, Fluid Beds, Hoppers, 1 ton – 3 ton Hoists, Granulators, Plastic Accessories and Chillers

Large Quantity of Power Tools including Drills, Chop Saws, Radial Arm Saw, Miter Saws, Circular Saws, Disc & Belt Sanders, Socket Sets, Laser Level Kits, Angle Grinders, Wrench Sets, Impact Wrenches, and accessories.

