


FOR LOS ANGELES SHIPMENTS ONLY	
Add to	Caterpillar Tractor Co.
	Trolley wired in Milwaukee for direct shipment to Customer
Order	Caterpillar Tractor Co.
	Trolley to be wired and tested in L.A. Plant

Plant Site	East Peoria, Illinois	Customer Project	☐ Main Spec.
Crane No.	C (H) -24011 F.C.E.	Specs. Released to:	☐ Eng. Service
		Inspection Dept.	☐ Elect. Engr.

Crane No.	C (H) -24011	F.C.E.	Inspection Dept.	☐	Elect. Engr.	☐
Spec. Date	Prop. No.	M-1026	Engr. Specs. Released by:	Estimator	Spec. Writer	Sales Desk
				BTS	CRS	CES



TROLLEY DATA		TYPE OF TROLLEY FRAME			
CAPACITY	LIFT	DRUM DIA.	REEVING	BRAKING	TYPE HOIST
15 Ton	30' - 0"	13 1/4"	8 x 1/2 (4P)	Dynagtorque	6EH
			x 270' 0"		

TYPE OF TROLLEY DRIVE		TYPE	
T-12	WHEELS	DIAMETER	F.S.R.T.
		12"	SPREAD 11' - 0"

BRIDGE DATA	TYPE OF SPAN CONDUCTORS	Festooned R.W. Track
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		
31		
32		
33		
34		
35		
36		
37		
38		
39		
40		
41		
42		
43		
44		
45		
46		
47		
48		
49		
50		
51		
52		
53		
54		
55		
56		
57		
58		
59		
60		
61		
62		
63		
64		
65		
66		
67		
68		
69		
70		
71		
72		
73		
74		
75		
76		
77		
78		
79		
80		
81		
82		
83		
84		
85		
86		
87		
88		
89		
90		
91		
92		
93		
94		
95		
96		
97		
98		
99		
100		

TYPE DRIVE	TH-15 (BR)	WHEELS	DIAMETER & NUMBER	TYPE
			15" 4	F.S.R.T.T.D.

FRONT PLATFORM	Full length Checkered Steel	TYPE OF GIRDERS	(2) welded box	TR. RAIL	30 LBS.

PLATEFORM	Short	OUTRIGGER	Trussed Handrail.
PLATEFORM	Short	OUTRIGGER	Trussed Handrail.

ELECTRICAL DATA		POWER SUPPLY		460	VOLTS AC 330		3	PHASE	60	CYCLE
	SPEED FT. PER MIN.	MOTOR DATA				MAKE & TYPE BRAKES		MAKE & TYPE LIMIT SWITCH		
		MFR.	FRAME	HP	RPM					
MAIN HOIST	15	P&H	HEWH324RX	15	1130	P&H	CDR	P&H DB100		
AUX. HOIST	100	P&H	HEW213-S	3	1675	P&H	CDR	& GLS		
TROLLEY	150	P&H	HEW 284RX	7½	845	P&H	HYD.			
BRIDGE										

MAKE	TYPE	CAB (OPEN)	(ENCL) (RH)	CAB ATTACH. TO	(BRIDGE)	XXXXXX
CONTROL	P&H	5 step V.S.	Full Magnetic	from Open Cab.		

PUNWAY DATA			
RAIL SIZE	60	LBS.	700'
COLLECTORS	Bull Dog	TR331-1	FURNISHED BY P&H
COND. TYPE	Bull Dog	TD310	Tandem
			RAIL TO ROOF 5'-8"
			RAIL TO FLOOR 24'-0"
			FURNISHED BY purchaser

Remarks: See Attached Addenda Paint: Orange HT-TH (BR) Milwaukee	MAIN HOIST ASSEM. 3100E1874-F512S		AUX. HOIST ASSEM. - - -		SUPPLEMENTAL EQUIPMENT SUPPLIED WITH CRANE Runway Conductors ☐ Spares ☐ Runway Stops ☐ ☐ ☐
	TROLLEY ASSEM. 3100E1054-F-197-S		BRIDGE ASSEM. 914E244-F38		
	ORDER		RECORDED		
	INSPECTION REQUIRED		DATE		
	YES ☐ NO ☐		SHIPPED		
	CRANE NO.		C(H)-24011		
	F.C.E.		F.C.E.		

FORM NO. 2266

* INCLUDES CAMBER

CAPACITY	15 TONS	H	2 FT.	8 IN.	R	5 FT.	8 IN.	AA	1 FT. 11½ IN.
LIFT	24'-10½" ACTUAL	J	2 FT.	0 IN.	S	1 FT.	0 IN.	BB	- FT. - IN.
A _{SPAN}	57 FT. 2 IN.	K	6 FT.	3 IN.	T	- FT.	- IN.	CC	- FT. - IN.
*B	5 FT. 5 IN.	L	7 FT.	6 IN.	U	- FT.	- IN.	<u>C(H)24011</u>	
C	0 FT. 5½ IN.	M	16 FT.	0 IN.	V	- FT.	- IN.		
*D	3 FT. 5¼ IN.	N	10 FT.	4½ IN.	W	- FT.	- IN.		
E	1 FT. 11¾ IN.	O	9 FT.	8½ IN.	X	- FT.	- IN.		
*F	4 FT. 6½ IN.	P	- FT.	- IN.	Y	10 FT.	5¼ IN.		
G	3 FT. 2 IN.	Q	24 FT.	IN.	Z	9 FT.	9¼ IN.		

Trolley Spread 11'-0"

MAXIMUM LOAD
PER WHEEL 28,000 lbs.

RUNWAY RAIL
A.S.C.E. PER YD. 60 LBS.

205.03 (11)
(THIS SKETCH REFERS TO DIMENSIONS, NOT CONSTRUCTION)

1. 1.2.2